



明達漆業(星)私人有限公司  
Brightex Paints (Singapore) Pte. Ltd.  
53 Tuas Avenue 1, Singapore 639502  
TEL: 6863 5411 FAX: 6863 5411  
EMAIL: enquiry53@brightexpaints.com

(Paints Manufacturer & Chemical Industrial Supplier)

Document No.: TDS-SB0026Rev01

Revised Date: 1/Nov/2016

TECHNICAL DATA SHEET FOR

## Betex Nitrocellulose Putty 22 (Grey)

<b>Description</b>	A ready mixed nitrocellulose hard putty	
<b>Recommended Use</b>	To fill shallow indentations for metal surfaces	
<b>Colour</b>	Grey	
<b>Characteristics</b>	<ul style="list-style-type: none"><li>• Fast Drying</li><li>• Minimum shrinkage</li><li>• Excellent abrasion</li><li>• Easy sanding</li></ul>	
<b>Technical Data</b>	Specific Gravity (25°C)	: 1.30 ± 0.10
	Flash Point	: 7°C
<b>Application Data</b>	Application Method	: Filled with putty knife
	Thinner	: Ready to use
<b>Directions of Use</b>	All surfaces should be clean, dry and free from contaminates. Apply Betex Nitrocellulose Putty 22 (Grey) on the affected area with putty-knife. Allow it to dry before sanding. Ensure the putty is thoroughly dry before applying any coatings.	
<b>Storage</b>	Should be tightly sealed and stored in cool, dry place. Keep away from open flames.	
<b>Packaging</b>	½ kg, 3 kg	
<b>Handling and Safety</b>	As it contains solvent, the product requires special care in handling. Avoid any eye and skin contact. For further information please refer to SDS.	
<b>Disclaimer</b>	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from	



明達漆業(星)私人有限公司

Brightex Paints (Singapore) Pte. Ltd.

53 Tuas Avenue 1, Singapore 639502

TEL: 6863 5411 FAX: 6863 5411

EMAIL: enquiry53@brightexpaints.com



(Paints Manufacturer & Chemical Industrial Supplier)

Document No.: TDS-SB0026Rev01

Revised Date: 1/Nov/2016

TECHNICAL DATA SHEET FOR

## Betex Nitrocellulose Putty 22 (Grey)

time to time, and without notice, in light of our experience and product development.