



明達漆業(星)私人有限公司
Brightex Paints (Singapore) Pte. Ltd.
53 Tuas Avenue 1, Singapore 639502
TEL: 6863 5411 FAX: 6863 5411
EMAIL: enquiry53@brightexpaints.com

(Paints Manufacturer & Chemical Industrial Supplier)

Document No.: TDS-SB0036 Rev01

Revised Date: 1/Nov/2016

TECHNICAL DATA SHEET FOR

Metex Rich Gold Paint No.58

Description	An acrylic based gold paint.	
Recommended Use	To be painted on wrought iron, steel and various substrates	
Colour	Gold	
Characteristics	<ul style="list-style-type: none">• Fast drying• Good adhesion• Excellent applicability	
Technical Data	Specific Gravity (25°C)	: 1.15 ± 0.05
	Flash Point	: 25°C
Application Data	Application Method	: Brush, Roll or Spray
	Dilution	: Ready to Use
Directions of Use	<ol style="list-style-type: none">1. Sand surface to remove oil, grease or dirt. (Washing or wiping with clean cloth using thinner is ideal).2. Stir the content thoroughly before use.3. Apply Metex Rich Gold Paint No.58 on the surfaces.	
Storage	Should be tightly sealed and stored in cool, dry place.	
Packaging	125 ml, 250 ml, 750ml	
Handling and Safety	As it contains solvent, the product requires special care in handling. Avoid any eye and skin contact. For further information please refer to SDS.	
Disclaimer	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.	