

(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Betex Plastic Wood

Document No.: TDS-SB0027Rev01 Revised Date: 1/Nov/2016

Description	A ready mixed, quick-dry wood patching compound
Recommended Use	To fill shallow indentations for metal surfaces
Colour	Teak & Natural
Characteristics	 Fast Dry Tough Good durability Good filling Easy sanding
Technical Data	Specific Gravity (25°C) : 0.95 ± 0.05 Flash Point : -4°C
Application Data	Application Method : Filled with putty knife Thinner : Ready to use
Directions of Use	All surfaces should be clean, dry and free from contaminates. Apply Betex Plastic Wood on the affected area with a putty-knife. Allow it to dry before sanding. Ensure the putty is thoroughly dry before applying any coatings.
Storage	Should be tightly sealed and stored in cool, dry place. Keep away from open flames.
Packaging	½ kg
Handling and Safety	As it contains solvent, the product requires special care in handling. Avoid any eye and skin contact. For further information please refer to SDS.
Disclaimer	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from



(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Betex Plastic Wood

Document No.: TDS-SB0027Rev01 Revised Date: 1/Nov/2016

time to time, and without notice, in light of our experience and product development.